



PRODUCT CODE:

Model 2551

REVISION:

16/01/2020

PAGE:

1 of 4

Potentiostat / Galvanostat

Model 2551

Table of Contents

1	General Description.....	1
2	Metrological Properties.....	2
2.1	Counter Electrode.....	2
2.2	Working Electrode.....	2
2.3	Reference Electrode.....	2
2.4	Polarization Capability.....	2
2.5	IR Compensation.....	2
2.6	Response Time.....	2
2.7	Meters and Interfaces.....	2
2.8	Digital Interface.....	3
2.9	Cell Connections.....	3
2.10	Power Supply and Dimensions.....	3
3	Implemented Electrochemical Techniques.....	3
3.1	Detection.....	3
3.2	Voltammetric.....	3
3.3	Stripping.....	4
4	Spare Parts.....	4



1 General Description

Model 2551 is the smallest potentiostat of AMEL's tabletop series. It has been conceived to be a perfect compromise between affordability and performances. The instrument is fully controlled by VApeak software for both electrochemical or electroanalytical techniques. AMEL's electrochemical equipment reliability stands on long time experience dating back to 1959.



2 Metrological Properties

2.1 Counter Electrode

Voltage Output	$\pm 19\text{V max}$
Current Output	$\pm 1,2\text{A max}$
Slew Rate	$0,01\text{mV/s to } 10\text{V/s}$
Protection	Thermal, overload and short-circuit

2.2 Working Electrode

Current Measure	From 10nA to 1A Full Scale in 9 ranges
Current Resolution	From 10pA at 10nA Full Scale to 100 μA at 1A Full Scale
Measuring Accuracy	$< 1\%$ of Full Scale in 10nA to 1 μA ranges $< 0,25\%$ of Full Scale in 10 μA to 1A range

2.3 Reference Electrode

Input Impedance	$> 1\text{T}\Omega$
Input Capacitance	$< 20\text{pF}$ (1m cable)
Biassing Current	$< 10\text{pA}$ at 25°C
Common Mode Rejection	$> 60\text{dB}$ full frequency response
Voltage Range	$\pm 10\text{V max}$
Input BNC	Grounded outer contact

2.4 Polarization Capability

Voltage	$\pm 10\text{V max}$
Current	$\pm 1\text{A max}$
Voltage Resolution	$0,1\text{mV}$
Current Resolution	10pA
Accuracy	$\pm 0,2\%$ & $0,1\%$ (conversion at Full Scale)

2.5 IR Compensation

Positive Feedback Range 2Ω to $100\text{M}\Omega$ (depending on current range)

2.6 Response Time

Potentiostatic Rise Time	$< 1\mu\text{s}$ resistive load (1000Ω)
Galvanostatic Rise Time	$< 17\mu\text{s}$ resistive load (1000Ω)



2.7 Meters and Interfaces

A/D Converter	16 BIT
D/A Converter	16 BIT
Temperature Meter	0 to +100°C with PT1000 probe (0,1°C resolution and $\pm 0,2^\circ\text{C}$ accuracy)
Sampling Rate	200 μs

2.8 Digital Interface

Connection	USB with full instrument control (baud rate 57600 – N – 8 – 1)
Memory	EEPROM 64kB – SRAM 32kB
Port Output	8 external accessories
I/O port	8 optional

2.9 Cell Connections

Cables	2, 3, 4 cables. BNC connector for Reference (Hi & Low) and PL258 for Working and Counter electrodes.
--------	--

2.10 Power Supply and Dimensions

Voltage Mains	115 or 230V AC $\pm 10\%$ 50/60Hz
Power Consumption	60VA max
Dimensions (L x W x H)	400 x 440 x 85mm
Weight	8kg

3 Implemented Electrochemical Techniques

3.1 Detection

AD	Amperometric Detection
PD	Potentiometric Detection
DSA	Double Step Amperometry
DSV	Double Step Potentiometry
PAD	Pulsed Amperometric Detection

3.2 Voltammetric

LSV	Linear Scan Voltammetry
CYV	Cyclic Voltammetry
GLV	Galvanostatic Linear Voltammetry
GCV	Galvanostatic Cyclic Voltammetry
SWV	Square Wave Voltammetry
NPV	Normal Pulse Voltammetry
ACV	Alternating Current Voltammetry

DPV Differential Pulse Voltammetry
DNV Differential Normal Pulse Voltammetry
DAV Differential Alternate Pulse Voltammetry

3.3 Stripping

LSS Linear Scan Stripping
ACS Alternate Current Stripping
SWS Square Wave Stripping
DAS Differential Stripping
DPS Differential Pulse Stripping
DNS Differential Normal Pulse Stripping
PSA Potentiometric Stripping Analysis
CCSA Constant Current Stripping Analysis

Spare Parts

191/GPC Grid power cable
191/USB USB cable
191/4BN4 Set of 4 WE, RE and CE cables
191/C4 Set of 4 crocodile clips for WE, RE and CE 4mm banana plugs

Distributor in Greece:



T. 210 72.43.529 - 6979 64.23.95
email: info@apples.com.gr
site: www.apples.com.gr