Frequency Response Analyzer

Model 2700 Z-Pulse

Table of Contents

1	General Description	1
2	Metrological Properties	2
	2.1 Arbitrary Waveform Generator	2
	2.1.1 Sine	2
	2.1.2 Square	
	2.1.3 Triangle	
	2.1.4 Pulse	
	2.1.5 Arbitrary	
	2.2 Power Supply, Connections and Dimensions	3
3	Snare Parts	



1 General Description

Model 2700 embeds the synergistic combination of impedance spectroscopy (Z) and high-speed pulse or waveform generation (pulse) paving the way to new and exciting possibilities in electrochemistry. AMEL's Frequency Response Analyzer pushes the researcher further in the investigation and characterization of supercapacitors and rechargeable batteries, electrochemical conversion for energy strorage, corrosion and corrosion protection studies, deposition of high-performances metal films, characterization of semiconductors and quality controls.

	PRODUCT CODE:	REVISION:	PAGE:
Electrochemistry	Model 2700	16/01/2020	2 of 3

2 Metrological Properties

2.1 Arbitrary Waveform Generator

2.1.1 Sine

 $\begin{array}{ll} \text{Frequency Range} & 1 \mu \text{Hz to 10MHz} \\ \text{Amplitde} & 20 \text{Vpp @1kHz} \\ \text{Noise} & \pm 0.1 \text{dB if} < 100 \text{kHz} \\ \end{array}$

 $\pm 0,15$ dB if < 5MHz $\pm 0,3$ dB if ≤ 10 MHz

2.1.2 Square

Frequency Range 1µHz to 10MHz

Rise & fall time 8ns
Overshoot < 1%

Duty Cycle 0,01% to 99,99%

Asimmetry < 0% of the period + 5ns @ 50% duty cycle

Jitter (RMS) < 50 ps

2.1.3 Triangle

Frequency Range 1µHz to 10MHz

Simmetry 0% to 100% in 0,1% steps

2.1.4 Pulse

 Period
 100ns to 1000s

 Pulse width
 15ns to 1000s

 Edge Time
 20ns to 1s

 Overshoot
 < 1%</td>

 Jitter (RMS)
 < 50ps</td>

2.1.5 Arbitrary

Frequency Range 1µHz to 10MHz

Sampling Rate 50MS/s DAC resolution 14bit

Output range ±12V at frequency < 10MHz

DC offset range ±12V at open circuit

Resolution 12 BIT

Accuracy 0,4% of range

PRODUCT CODE:	REVISION:	PAGE:
Model 2700	16/01/2020	3 of 3

2.2 Power Supply, Connections and Dimensions

Computer Connection Universal Serial Bus (USB)
Voltage Mains 12 to 24V DC, 1A max

External Power Model 2560 8-channel Power Supply

Single Power Supply (provided if Model 2560 is not present)

Dimensions (L x W x H) 200 x 215 x 80mm

Weight 1,5kg

\$ Spare Parts

191/SUPS24 Power supply for single unit 191/BNCFRASet of 3 BNC cables for connection with potentiostats 191/DUMMY Dummy cell for Frequency Response Analyzer

Distributor in Greece:



T. 210 72.43.529 - 6979 64.23.95 **email:** info@apples.com.gr **site:** www.apples.com.gr